Specifications:
Housing:High temperature plastic UL94V-0;Color:natural
Latch:High temperature plastic UL94V-0;Color:black
Terminal:Copper alloy, Matte Tin/Gold
Fitting Nail:Copper alloy, Matte Tin
Product must comply HF RoHS specification
Contact resistance:≤30mΩ
Insulation resistance:≥100MΩ
Rated voltage:50V AC/DC
Rated current:0.5A AC/DC
Withstand Voltage:250V AC/minute
Temperature Range:-55°C~+105°C

ORDER INFORMATION:

F0504AWR-**-F4M*1-*

PART No.
No.OF CIRCUITS: 4~50
PLASTIC MATERIAL: F4M=LCP(Natural)
Metal code: 1=Phosphor Bronze
PLATING: B=Matte Tin C=
PACKAGING: R=REEL G=TUBE

JKUN WENZHOU JKUN CONNECTOR CO.,LTD.			
GENERAL TOLERANCE		USE: CUSTOMER	TITLE: FPC Pitch0.5 H1.0 Back-Flip Conn.
X.X ±0.15	X. ±5°	APPD: Shaojinghe	PART NO.:
X.XX ±0.10	X.X ±2°	CHKD: Shaojinghe	DWG NO.:
X.XXX ±0.05	X.XX ±1°	DR: Ryan	SCALE / SHEET
	UNITS: mm		