

-
↓

Specifications:

Contact resistance: $\leq 20\text{m}\Omega$
Insulation resistance: $\geq 1000\text{M}\Omega$
Rated voltage: 350V AC DC
Rated current: 3.0A AC DC
Withstand voltage: 500V Δ

Si_____

A

B

C

D

E

F

1

1

2

2




3

3

4

4

5

JKUN WENZHOU JKUN CONNECTOR CO.,LTD.			TITLE:	
GENERAL TOLERANCE		USE:	PART NO.:	
X. ±0.50	X. ±5°	APPD:	DWG NO.:	
X.X ±0.30	X.X ±2°	CHKD:	SCALE	
X.XX ±0.20	X.XX ±1°	DR:	SHEET	
		UNITS: mm		

A

B

C

D

E

F

A

B

C

D

E

F

1

1

2

2


3

3

4

4

5

JKUN WENZHOU JKUN CONNECTOR CO.,LTD.			TITLE:	
GENERAL TOLERANCE		USE:	PART NO.:	
X. ±0.50	X. ±5°	APPD:	DWG NO.:	
X.X ±0.30	X.X ±2°	CHKD:	SCALE	
X.XX ±0.20	X.XX ±1°	DR: 符	SHEET	
 UNITS: mm				

A

B

C

D

E

F

包装说明:

1. 把成品包入卷盘中，

1

2

ε

AAAAAAAA

ÆÁÄ